

# HENRY®

The Professional's Formula For Success™

# Patch & GO

Dries In As Little As **15** Minutes!



Specially formulated for smoothing and patching interior and exterior surfaces prior to sealing, wallpapering, staining or painting.



#### Versatile

Use over wood, concrete, plaster, block wall, masonry, brick, drywall, paneling, ceramic tile, metal & stucco

#### Infinite Applications

Can be molded, shaped, carved, sanded, screwed, nailed, smoothed, stained, painted or used to set ceramic tile

#### Dries Quickly

Paint or seal in as little as 15 minutes

#### Highly Durable

Moisture and mildew resistant - will not shrink

#### Indoor & Outdoor Usage

For almost any surface

#### Solvent-Free

For safer installations

**Multipurpose Patch,  
Repair & Resurfacer**

**REPAIR, PATCH & FILL ALMOST ANY SURFACE!**

# HENRY® Patch & Go

**The Professional's Formula For Success when smoothing and patching interior and exterior surfaces prior to sealing, wallpapering, staining, or painting. Use Patch & Go to fill and smooth exterior surfaces such as concrete and wood, as well as interior floor and wall surfaces prior to painting or sealing.**

HENRY Patch & Go is specially formulated for smoothing and patching interior and exterior surfaces prior to sealing, wallpapering, staining or painting. Use HENRY Patch & Go to fill and smooth exterior surfaces such as concrete or wood, as well as interior floor and wall surfaces prior to painting or sealing. HENRY Patch & Go is easy to apply, hardens quickly, does not shrink, can repair wood rot, be molded, shaped, carved, sanded, screwed, nailed or smoothed to produce a surface finish which can be painted or sealed in 15 minutes!

HENRY Patch & Go mixes with water only to a creamy, smooth consistency for easy application over a variety of common building surfaces including concrete, masonry, wood, plaster, ceramic tile and drywall. Engineered with Portland cement, HENRY Patch & Go is tougher and more durable than gypsum, latex or putty-type patches. HENRY Patch & Go can be used as a setting material for replacing broken or missing ceramic tile. HENRY Patch & Go dries internally, permitting the finishing coat of paint, sealer or stain to be applied as soon as the surface is hard - less waiting time means the job is finished faster!

HENRY Patch & Go is intended for interior and exterior applications that will receive a suitable coating of paint, sealer, or other wall covering. Do not use in areas that will be subjected to standing water or permanent moisture. Do not allow repair surfaces to be exposed to rain or moisture prior to sealing or painting.

## **SURFACES:**

### **Use HENRY Patch & Go Over:**

- Wood
- Concrete
- Plaster
- Ceramic Tile
- Masonry
- Brick
- Drywall
- Paneling
- Metal
- Stucco

## **RANGE OF APPLICATION:**

- Use HENRY Patch & Go to fill in surface defects such as spalls, gouges, cracks, dents, chips, bugholes, honeycombs, wood rot - any type, size or shape of surface defect that needs to be filled and smoothed before coating. Use HENRY Patch & Go for filling and smoothing exterior concrete walls, whether poured in place, tilt-up or masonry block. HENRY Patch & Go is suitable for smoothing wood windowsills, framing thresholds and molding prior to painting, staining or sealing the surface. HENRY Patch & Go can also be used as a setting material for re-adoring broken or missing ceramic tile (small repair only).

## **RECOMMENDED TOOLS:**

Mixing bucket, margin trowel, trowel, or putty knife. HENRY Patch & Go can be mixed using a mixing stick or a mechanical mixing paddle and a drill.

## **TECHNICAL DATA:**

- Pot life: 15-20 minutes at 70°F. Pot life varies based on surrounding temperatures.
- Color: White, Portland cement. As with any natural cementitious product, variations in color can occur.
- Packaging: 1 lb. tubs and 7 lb. pails
- Storage: Reseal and store in a cool, dry area.
- Shelf Life: One year in original unopened container.

## **SURFACE PREPARATION:**

### **Preparation:**

- Read installation instructions thoroughly prior to installation.
- All existing surfaces that are to receive patching or smoothing must be clean, sound, solid, and free of weak or loose areas, dust, dirt, oil, or any contaminant that may act as a bond breaker.
- Remove flaking or deteriorating coats of paint. Sealers should be removed. When necessary, surface preparation must be by mechanical means, such as a chisel or sanding. Do not use solvents or acids.
- When repairing wood rot, completely remove rotting portion of wood prior to repairing with HENRY Patch & Go.
- When re-adoring ceramic tile, use for small repairs only. Remove all old setting material from substrate and tile prior to proceeding with repair.
- Surfaces to receive HENRY Patch & Go must be a minimum of 50°F (10°C).

## **MIXING:**

- Combine 2 parts powder to 1 part of water (by volume). For 1 lb. of HENRY Patch & Go, use 1 cup (8 oz.) of water. NOTE: The use of additional water will weaken HENRY Patch & Go and lower its durability. Mix only as much Henry Patch & Go as you can place in 15 minutes. Use cool water to mix. Warm or hot water may cause material to set up faster. Cold water may cause material to dry slower.
- Use slightly less water for a thicker patch consistency for deep filling.
- Place the water in the mixing container first and then add the powder while mixing by hand to a lump-free consistency. NOTE: Mixing with a drill will produce a creamier and smoother consistency.

## **INSTALLATION:**

- HENRY Patch & Go is easily applied to any prepared surface. Use a putty knife for small areas and a flat trowel for large surfaces. Apply sufficient pressure to fill in all surface defects.

- Where necessary, minor touch up work can be accomplished by using a slightly dampened sponge once the surface has hardened to obtain a smooth surface. If the material has already dried, the surface can be smoothed with fine sand paper.
- When using HENRY Patch & Go to re-adhere loose or disbonded tile, scrape the existing adhesive off of the tile and the substrate. Apply a sufficient layer of HENRY Patch & Go to the back of the tile using a properly notched trowel. Press tile firmly into place and allow tile to fully set before grouting.

## **THICKNESS OF INSTALLATION:**

Since HENRY Patch & Go contains no sand or gritty filler, it can be smoothed to a true featheredge for perfectly smooth transitions. In addition, HENRY Patch & Go can be used in small areas to fill gouges, dents, and holes, at depths of 1" or greater. Please note that thicker areas will take longer to harden.

## **DRYING:**

HENRY Patch & Go requires no special curing or drying procedures. In fact, due to its unique formulation, application of a latex paint or water-borne sealer can begin as soon as the surface has hardened. It does not need to be completely dry. The time until the surface hardens will vary with jobsite conditions, weather, type of substrate, and thickness of installation. Smoothing over small voids in plaster, wood, or drywall may require 15 minutes of drying time, while thicker applications, as well as those outdoors at cooler temperatures, may take longer.

## **SATISFACTION GUARANTEE:**

The W.W. Henry Company guarantees that this product will meet your satisfaction. If not, we will refund the purchase price of the material with proof of purchase. This guarantee does not include labor or the cost of labor for the installation of this product, or any direct, indirect, incidental, or consequential damages. This guarantee is valid only for product used within the stated shelf-life. No other warranty is expressed or implied.

## **WARNINGS:**

**⚠WARNING! INJURIOUS TO EYES! CAUSES SKIN IRRITATION!** Contains Portland cement. Avoid eye contact or prolonged contact with skin. Wash thoroughly after handling. In case of eye contact, flush repeatedly with water for at least 15 minutes. Consult a physician immediately. **KEEP OUT OF THE REACH OF CHILDREN!**

The W.W. Henry Company  
400 Ardex Park Drive  
Aliquippa, PA 15001  
Customer Service: 1-800-232-4832  
[www.wwhenry.com](http://www.wwhenry.com)  
[www.patchandgo.com](http://www.patchandgo.com)

# REPAIR, PATCH & FILL ALMOST ANY SURFACE!